

2015

DYNACARGO[®]

TRUCK TIRE CATALOG



DYNACARGO[®]

QUALITY AND VALUE FOR EVERY APPLICATION



MISSION

DYNACARGO is dedicated to providing the highest quality and value to our customers. Each tire is built to perform, using advanced technology and innovation in an ISO9001 certified factory to provide consistent quality.

DYNACARGO brings you an ever-increasing selection of commercial truck tires – from steer, all-position and trailer to mixed service tread designs. Whether you are looking for a Regional, Line-Haul or On/Off Road application, DYNACARGO has you covered. Plus, every tire is backed by a comprehensive warranty.

DYNACARGO brings you quality and value with every tire.



SIZE CHART

SIZE	STEER ALL-POSITION		TRAILER		DRIVE				MIXED SERVICE				WIDE BASE	
	Y208 FE	Y201 FE / Y201	Y202 FE	Y203	Y103	Y101	Y105	Y501	Y601	Y131	Y205	Y866	Y603	Y631
215/75R17.5				H										
235/75R17.5				H										
225/70R19.5		F/G						G						
245/70R19.5		H						G						
265/70R19.5		H												
9.00R20									H					
10.00R20									H			J		
11.00R20									J					
12.00R20									J					
255/70R22.5				H										
275/70R22.5				H										
295/60R22.5		J												
295/75R22.5	G	G*	G		G	G								
11R22.5	G/H	G/H*	G		G/H	G/H	H		H	H	H			
295/80R22.5		J				J								
12R22.5		J				J	J		J		J			
315/80R22.5		J				J	J		J/M		J			
13R22.5							J				J			
385/65R22.5													L	L
425/65R22.5														L
12.00R24									L		L			
285/75R24.5	G	G*	G		G	G								
11R24.5	G/H	G/H*	G		G/H	G/H			H	H				

*FE version

TABLE OF CONTENTS

STEER ALL-POSITION

Y208 FE	DECOUPLING GROOVE STEER	1
Y201 FE	STEER/ALL-POSITION.....	1
Y201	STEER/ALL-POSITION.....	2

TRAILER

Y202 FE	SHALLOW DEPTH TRAILER	2
Y203	ALL-POSITION.....	2

DRIVE

Y103	CLOSED SHOULDER DRIVE.....	3
Y101	OPEN SHOULDER DRIVE.....	3
Y105	REGIONAL LOW PROFILE DRIVE	4
Y501	REGIONAL DRIVE.....	4

MIXED SERVICE

Y601	ON/OFF-HIGHWAY ALL-POSITION	4
Y131	ON/OFF-HIGHWAY DRIVE.....	5
Y205	STEER/ALL-POSITION.....	5
Y866	ON/OFF HIGHWAY DRIVE	5

WIDE BASE

Y603	FREE-ROLLING WIDE BASE	6
Y631	WIDE BASE ON/OFF-HIGHWAY	6

Y208 FE

 DECOUPLING GROOVE STEER

FEATURES & BENEFITS

- 5-rib tread design with special tread compounds enhances even wear, traction in line-haul steer axle positions
- Rock ejectors to prevent stone damage and improve casing durability
- Multiple sipes and shoulder decoupling grooves enhance tire wear and traction
- The 19/32" tread depth promotes long original tread life
- SmartWay Verified for improved Fuel Efficiency (FE)

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213889255	295/75R22.5	14	TL	9.00	19	40.6	11.7	6175/5675	110/110	M	144/141	117
1213881255	11R22.5	14	TL	8.25	19	41.4	11.0	6175/5840	105/105	M	144/142	118
1213881256	11R22.5	16	TL	8.25	19	41.4	11.0	6610/6005	105/105	M	146/143	118
1213888455	285/75R24.5	14	TL	8.25	19	41.5	11.1	6175/5675	110/110	M	144/141	120
1213881455	11R24.5	14	TL	8.25	19	43.3	11.0	6610/6005	105/105	L	146/143	128
1213881456	11R24.5	16	TL	8.25	19	43.3	11.0	7160/6610	120/120	L	149/146	128

Y201 FE

 STEER/ALL-POSITION

FEATURES & BENEFITS

- 5-rib tread design with wide shoulders provides for durability and even wear in steer/all-position tire applications
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions
- Deep original tread depth provides long original tread life
- SmartWay Verified for improved Fuel Efficiency (FE)

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213819255	295/75R22.5	14	TL	9.00	19	40.6	11.7	6175/5675	110/110	M	144/141	117
1213811255	11R22.5	14	TL	8.25	19	41.4	11.0	6175/5840	105/105	M	144/142	118
1213811256	11R22.5	16	TL	8.25	19	41.4	11.0	6610/6005	105/105	M	146/143	118
1213818455	285/75R24.5	14	TL	8.25	19	41.5	11.1	6175/5675	110/110	M	144/141	120
1213811455	11R24.5	14	TL	8.25	19	43.3	11.0	6610/6005	105/105	L	146/143	128
1213811456	11R24.5	16	TL	8.25	19	43.3	11.0	7160/6610	120/120	L	149/146	128

Y201

STEER/ALL-POSITION



FEATURES & BENEFITS

- 5-rib tread design with wide shoulders provides for durability and even wear in steer/all-position tire applications
- Enhanced siping and wide grooves allows for premium traction in both wet and dry conditions
- Deep original tread depth provides long original tread life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213282275	225/70R19.5	12	TL	6.75	16	31.9	8.9	3640/3415	95/95	M	125/123	66
1213282276	225/70R19.5	14	TL	6.75	16	31.9	8.9	3969/3748	110/110	M	128/126	66
1213284796	245/70R19.5	16	TL	7.50	16	33.0	9.8	4940/4675	120/120	L	136/134	81
1213286796	265/70R19.5	16	TL	7.50	16	34.3	10.0	6005/5675	123/123	K	143/141	64
1213289254	295/60R22.5	18	TL	9.00	20	36.5	11.5	7390/6780	130/130	L	150/147	106
1213289258	295/80R22.5	18	TL	9.00	19	41.2	11.7	7830/7160	130/130	M	152/149	122
1213282258	12R22.5	18	TL	9.00	21	42.7	11.8	7830/7160	135/135	L	152/149	134
1213281257	315/80R22.5	18	TL	9.00	20	42.5	12.2	8820/7830	120/120	M	156/152	141

Y202 FE

SHALLOW DEPTH TRAILER



FEATURES & BENEFITS

- 5-rib design promotes premium handling, stability and traction
- Optimum tread design promotes even wear in free rolling and trailer axle positions
- Enhanced siping provides traction and fights irregular wear
- SmartWay Verified for improved Fuel Efficiency (FE)

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213829255	295/75R22.5	14	TL	9.00	12	40.2	11.7	6175/5675	110/110	M	144/141	102
1213821255	11R22.5	14	TL	8.25	12	41.0	11.0	6175/5840	105/105	M	144/142	106
1213828455	285/75R24.5	14	TL	8.25	12	41.1	11.1	6175/5675	110/110	L	144/141	110
1213821455	11R24.5	14	TL	8.25	12	42.9	11.0	6610/6005	105/105	L	146/143	114

Y203

ALL-POSITION



FEATURES & BENEFITS

- 5-rib design promotes traction and long life
- Special tread compounds allow for long life in trailer and all position applications
- Solid shoulder to resist irregular wear and curb damage

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213391776	215/75R17.5	16	TL	6.00	16	30.2	8.3	4805/4540	125/125	L	135/133	61
1213396795	235/75R17.5	16	TL	6.75	16	31.4	9.2	6010/5680	125/125	L	143/141	70
1213395726	255/70R22.5	16	TL	7.50	13	36.6	10.0	5510/5070	120/120	N	140/137	88
1213397726	275/70R22.5	16	TL	8.25	16	37.7	10.9	6940/6395	130/130	M	148/145	108



FEATURES & BENEFITS

- Closed shoulder tread design provides even wear, while maintaining excellent traction
- Heavy-duty casing for strength, stability, toughness and multiple retreads
- Extra deep 30/32" tread depth promotes long original tread life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213489255	295/75R22.5	14	TL	9.00	30	40.2	11.7	6175/5675	110/110	L	144/141	121
1213481255	11R22.5	14	TL	8.25	30	41.9	11.0	6175/5840	105/105	L	144/142	129
1213481256	11R22.5	16	TL	8.25	30	41.9	11.0	6610/6005	120/120	L	146/143	129
1213488455	285/75R24.5	14	TL	8.25	30	41.6	11.1	6175/5675	110/110	L	144/141	127
1213481455	11R24.5	14	TL	8.25	30	43.9	11.0	6610/6005	105/105	L	146/143	138
1213481456	11R24.5	16	TL	8.25	30	43.9	11.0	7160/6610	120/120	L	149/146	138



FEATURES & BENEFITS

- Open shoulder design provides excellent traction in wet/dry conditions
- Enhanced siping provides traction and fights irregular wear
- Deep 26/32" tread depth for long original mileage

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213419255	295/75R22.5	14	TL	9.00	25	40.9	11.7	6175/5675	110/110	L	144/141	122
1213411255	11R22.5	14	TL	8.25	25	41.7	11.0	6175/5840	105/105	M	144/142	123
1213411256	11R22.5	16	TL	8.25	25	41.7	11.0	6610/6005	120/120	M	146/143	123
1213419258	295/80R22.5	18	TL	9.00	28	41.8	11.7	7830/7160	130/130	M	152/149	130
1213412258	12R22.5	18	TL	9.00	28	43.0	11.9	7830/7160	135/135	L	152/149	156
1213411257	315/80R22.5	18	TL	9.00	28	43.2	12.5	8820/7830	120/120	L	156/150	161
1213418455	285/75R24.5	14	TL	8.25	25	41.9	11.1	6175/5675	110/110	L	144/141	126
1213411455	11R24.5	14	TL	8.25	25	43.7	11.0	6610/6005	105/105	L	146/143	135
1213411456	11R24.5	16	TL	8.25	25	43.7	11.0	7160/6610	120/120	L	149/146	135

**FEATURES & BENEFITS**

- Innovative tread design and compounds promotes excellent traction and to resist irregular wear
- Durable casing construction is perfect for tough regional and urban use
- Deep original tread depth provides maximum tread life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1214901256	11R22.5	16	TL	8.25	25	41.9	11.0	6610/6005	120/120	L	146/143	123
1214902258	12R22.5	18	TL	9.00	25	43.2	11.9	7830/7160	135/135	L	152/149	160
1214901257	315/80R22.5	18	TL	9.00	25	42.5	12.2	8270/7610	120/120	M	154/151	161
1214903227	13R22.5	18	TL	9.75	26	44.7	12.6	8270/7610	120/120	K	154/151	160

**FEATURES & BENEFITS**

- Innovative open shoulder tread design provides enhanced traction in multiple applications
- Enhanced siping provides traction and fights irregular wear
- The 19/32" tread depth promotes long original tread life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213612796	225/70R19.5	14	TL	6.75	19	32.6	8.8	3970/3750	110/110	L	128/126	68
1213614795	245/70R19.5	14	TL	7.50	19	33.5	9.6	4540/4300	110/110	L	133/131	84
1213616796	265/70R19.5	16	TL	7.5	22	34.6	10	6005/5675	123/123	L	143/141	86

**FEATURES & BENEFITS**

- Shoulder design promotes traction and vehicle stability
- Special cut, chip & tear resistant tread compound for longer wear and excellent performance
- Heavy duty casing construction provides added durability in tough applications

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	INFLATION PRESSURE (PSI)	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213999206	9.00R20	16	TT	7.00	19	40.1	10.2	6170/5840	130/130	K	144/142	110
1213991028	10.00R20	16	TT	7.50	21	41.5	10.9	6610/6010	120/120	K	146/143	140
1213991208	11.00R20	18	TT	8.00	21	42.7	11.5	7830/7160	135/135	K	152/149	155
1213991408	12.00R20	18	TT	8.50	22	44.3	12.4	8270/7610	120/120	K	154/151	164
1213991256	11R22.5	16	TL	8.25	19	41.4	11.0	6610/6005	105/105	M	146/143	118
1213992258	12R22.5	18	TL	9.00	21	42.7	11.8	7830/7160	135/135	L	152/149	134
1213991257	315/80R22.5	18	TL	9.00	20	42.5	12.2	8820/7830	120/120	M	156/152	141
1213991259	315/80R22.5	22	TL	9.00	20	42.5	12.2	10000/9090	130/130	J	160/157	141
1213992248	12.00R24	20	TT	8.50	20	48.0	12.2	9920/9090	130/130	K	160/157	149
1213991456	11R24.5	16	TL	8.25	19	43.3	11.0	7160/6610	120/120	L	149/146	128

Y131

ON/OFF-HIGHWAY DRIVE



FEATURES & BENEFITS

- Aggressive tread offers excellent traction for severe off-highway use
- Chip and cut resistant compounds offer long mileage and wear, while reducing effect of cuts, snags and tears
- Extra deep 33/32" tread depth for long original mileage

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213491256	11R22.5	16	TL	8.25	33	43.0	11.1	6610/6005	120/120	G	146/143	129
1213491456	11R24.5	16	TL	8.25	33	44.0	11.1	7160/6610	120/120	G	149/146	138

Y205

STEER/ALL-POSITION



FEATURES & BENEFITS

- Solid shoulder to resist irregular wear and curb damage
- The 20/32" tread depth promotes long original tread life
- Tire, tube and flap included

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213271256	11R22.5	16	TL	8.25	22	41.4	11.0	6610/6005	120/120	L	146/143	121
1213272258	12R22.5	18	TL	9.00	22	42.7	11.8	7830/7160	135/135	L	152/149	133
1213271257	315/80R22.5	18	TL	9.00	22	42.5	12.2	8820/7830	120/120	M	154/151	141
1213273227	13R22.5	18	TL	9.75	22	42.4	12.6	8270/7610	120/120	K	154/151	155
1213272248	12.00R24	20	TT	8.50	20	48.0	12.2	9920/9090	130/130	K	160/157	150

Y866

ON/OFF-HIGHWAY DRIVE



FEATURES & BENEFITS

- Deep shoulder blocks eject mud and water for improved off-road traction
- Directional tread design increases biting edges for confident rough-terrain handling
- Angled tread blocks act as self-cleaning agents for better grip and longer tire life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213731028	10.00R20	18	TT	7.50	24	41.5	10.9	7160/6610	135/135	K	149/146	150

Y603**FREE-ROLLING WIDE BASE****FEATURES & BENEFITS**

- Tread pattern and heavy ply rating designed for multiple uses
- 6-Rib design excellent for free rolling applications
- Durable casing provides long original tread life and promotes multiple retreads

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1213648258	385/65R22.5	20	TL	11.75	20	42.0	14.8	9920	130	K	160	164

Y631**WIDE BASE ON/OFF-HIGHWAY TIRE****FEATURES & BENEFITS**

- Innovative open shoulder design provides excellent traction in multiple applications
- Enhanced siping provides traction and fights irregular wear
- The 19/32" tread depth promotes long original tread life

ARTICLE NO.	TIRE SIZE	PLY RATING	TYPE	RIM (INCH)	TREAD DEPTH (32ND/INCH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	MAX LOAD (LBS) SINGLE/DUAL	PSI SINGLE/DUAL	SPEED SYMBOL	LOAD INDEX	WEIGHT (LBS)
1216318258	385/65R22.5	20	TL	11.75	22	42.2	14.8	9920	130	K	160	164
1216312258	425/65R22.5	20	TL	13.00	22	44.6	16.3	11400	120	K	165	199

DYNACARGO[®]

QUALITY AND VALUE FOR EVERY APPLICATION

dynacargotires.com • tbcbrands.com • treadxpress.com • 1-866-822-4968

Distributed and Marketed by

TBCBrands

4300 TBC Way, Palm Beach Gardens, FL 33410

Dynacargo is the registered trademark of TBC Corporation