



青岛启航轮胎有限公司
QINGDAO QIHANG TYRE CO., LTD.

青岛启航轮胎有限公司
QINGDAO QIHANG TYRE CO., LTD.

Factory add: Mingcun Town, Pingdu City,
Qingdao China.

Office: RM902, Suite A, Jinhua Apartment,
No.100 Nanjing Road, QingDao China.

TEL: (0086)-(0532)- 85831197, 86321777

FAX: (0086)-(0532)- 85831187, 86323517

HTTP: // www.qihangtyre.com.cn

E-MAIL: manager@qihangtyre.com.cn

INTRODUCTION

Qingdao Qihang Tyre Co., Ltd is one of the leading tyre factory with strong strength in China. we have advanced laboratory and inspection system ,and more than thirty tyre experts and professionals, which will provide dynamic impetus for the tyre developing and improving timely.

We mainly produce Agricultural & Implement tyres, all various Industrial & Off-The-Road tyres, Truck and Light truck Trailer tyres. the "ROADGUIDER" "FORERUNNER" brand tyres with highly guaranteed quality and the most competitive price are enjoying better and better reputation in oversea market, especially in North and South America and European countries.

"High Quality, Perfect Service, Reasonable Price " are always the subject adhere to, even regard this principle as our life.

We also dedicate to continually expand and update our product range provided with adding new lines and sizes to meet the changing inquiry in the world market.

We are anticipating a mutual win business with all of our business partners.



ROADGUIDER

FORERUNNER



青島启航轮胎有限公司

Excavator Tires

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
8.25-20 TT	14	992	245	6.50	2060	675
9.00-20 TT	14	1030	260	7.00	3000	700
10.00-20 TT	16	1062	280	7.50	3000	810



QH107

Agricultural & Implement Trailer Tires

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
11L-16	10	838	279	8	1250	420
11L-15	8	813	279	8	1060	360



F3

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Inflated Pressure (kpa)
4.00-12	4	535	110	3.00D	340
4.00-19	4	720	110	3.00D	340
5.00-15	4	665	140	4J	420
5.50-16	8	710	150	4.00E	370
6.00-16	8	740	160	4.00E	450
6.50-16	8	750	175	4.50E	420
7.5L-15	8	745	208	6LB	370
7.50-16	8	810	205	5.50F	370
7.50-16	10	810	205	5.50F	370
7.50-18	8	860	205	5.50F	370
7.50-20	8	910	205	5.50F	370
9.5L-15	8	780	240	8LB	310
11L-15	8	810	280	8LB	340
10.00-16 3RIB	10	910	275	W8L	340
10.00-16 4RIB	10	910	275	W8L	340
11.00-16 3RIB	10	970	315	W10L	310
11.00-16 4RIB	12	970	315	W10L	310



F2

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Inflated Pressure (kpa)
760L-15	8	734	193	5.5	360
9.5L-15	8	780	240	8LB	280
9.5L-14	8	741	241	7.00	300
11L-15	8	810	280	8LB	280
11L-15	12	810	280	8LB	280
11L-14	8	750	280	8LB	280
11L-16	8	835	280	8LB	280
12.5L-15	12	823	318	10.00	360



I-1

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Inflated Pressure (kpa)
4.00-12	4	535	112	3.00D	240
5.00-12	6	590	145	4.00E	200
6.00-16	8	690	165	4.50E	250
6.50-16	8	765	180	4.50E	250
7.50-16	8	810	205	5.50F	210
7.50-20	8	910	205	5.50F	240
9.50-20	8	950	240	W8	210
8.3-24	8	995	210	W7	240
9.5-24	8	950	240	W8	210
11.2-24	8	1105	285	W10	240
11.2-28	8	1495	284	W10	120
11.2-38	8	1459	284	10.00	120
12.4-24	8	1160	315	W11	230
12.4-28	8	1260	315	W11	230
13.6-24	8	1210	345	W12	200
13.6-28	8	1310	345	W12	200
14.9-24	8	1265	378	W13	180
14.9-28	8	1365	378	W13	230
15.5-38	10	1570	395	DW14	230
16.9-28	8	1435	430	W15L	200
16.9-30	8	1485	430	W15L	200
16.9-34	10	1585	430	W15L	200
18.4-30	10	1550	467	W16L	180
18.4-34	10	1888	457	W16L	180
18.4-38	10	1755	467	W16L	210
20.8-38	10	1835	528	W18L	270



R-1

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Inflated Pressure (kpa)
18.4-30	10	1550	467	W16L	230
18.4-34	10	1655	467	W16L	230
18.4-38	10	1755	467	W16L	180



Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Inflated Pressure (kpa)
11.2-38	6	1420	260	10	125
14.9-24	6	1265	378	W13	140

Irrigation Tire

R2



Skid Steer (Rim Guard) Tubeless

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10-16.5	10	779	261	8.25	2170	520
12-16.5	12	830	312	9.75	2900	550
14-17.5	14	922	351	10.5	3875	550
15-19.5	14	1029	391	11.75	4565	485

SKS-1



Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10-16.5	12	795	279	8.25	2140	520
12-16.5	14	835	325	9.75	2885	550

SKS-2



Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10-16.5	12	773	264	8.25	2135	520
12-16.5	14	831	307	9.75	2865	550

SKS-3



SKS-4

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10-16.5	12	820	264	8.25	1930	520
12-16.5	14	831	325	9.75	2865	550



SKS-5

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
27*8.5-15	6	691	259	8.5	1080	310
27*10.5-15	6	678	213	7JA	1030	310
23*8.5-12	6	574	213	7.00	820	340



SKS-5

Bias Truck Trailer Tire

RG036

Size	Ply	Rim	Maximum Load(lbs)		Pressure (Psi)		Load Range	Type
			Single	Dual	Single	Dual		
11-22.5	14	8.25	6175	5750	100	90	G	Tubeless



RG037

Size	Ply	Rim	Maximum Load(lbs)		Pressure (Psi)		Load Range	Type
			Single	Dual	Single	Dual		
1000-20	14	7.50	6175	5750	100	90	G	Tube Tire



RG038

Size	Ply	Rim	Maximum Load(lbs)		Pressure (Psi)		Load Range	Type
			Single	Dual	Single	Dual		
11-22.5	14	8.25	6175	5750	100	90	G	Tubeless



Mobile Home Tubeless

MH400

Size	Ply	Overall Diameter (mm)	Inflated Pressure (kpa)	Section Width(mm)	Rim	Load Capacity (kgs)	Max.Speed
8-14.5	14	706	420	203	6.00MH	1380	90km/h

Bias Trailer Tire

QH500

Wheel Diameter (inches)	Metric Tire Size	Load in KG Minimum	Load Range Load Index	Ply Rating Minimum	Overall Diameter mm	Tire Width mm	Max PSI LBS rated
13	175/80D	615	C	6	610	177	50
14	205/75D	800	C	6	664	203	50
15	205/75D	825	C	6	689	203	50
15	225/75D	1150	D	8	719	223	65



QH501

Wheel Diameter (inches)	Metric Tire Size	Load in KG Minimum	Load Range Load Index	Ply Rating Minimum	Overall Diameter mm	Tire Width mm	Max PSI LBS rated
15	205/75D	825	C	6	689	203	50



RG034

Wheel Diameter (inches)	Metric Tire Size	Load in KG Minimum	Load Range Load Index	Ply Rating Minimum	Overall Diameter mm	Tire Width mm	Max PSI LBS rated
16	7.50-16	1250	E	10	850	215	75



RG035

Wheel Diameter (inches)	Metric Tire Size	Load in KG Minimum	Load Range Load Index	Ply Rating Minimum	Overall Diameter mm	Tire Width mm	Max PSI LBS rated
15	700-15	1650	E	10	750	200	75
16	750-16	1395	F	12	850	215	90
16	750-16	1250	E	10	850	215	75



TIRE SIZE TUBELESS	LOAD RANGE/PLY	TIRE DIAMETER INCHES	SECTION WIDTH INCHES	MAX LOAD LBS	INFLATION PSI	WEIGHT LBS	RIM WIDTH INCHES
4.80-8	B(4)	16.30	4.92	738	59	5.13	3.75
4.80-8	C(6)	16.30	4.92	838	88	5.43	3.75
5.70-8	B(4)	18.43	5.83	715	50	8.56	3.75
5.70-8	C(6)	18.94	5.94	910	75	8.93	3.75
5.70-8	D(8)	18.94	5.94	1075	100	10.01	3.75
4.80-12	B(4)	18.94	5.94	780	60	8.76	4.00
4.80-12	C(6)	21.06	4.92	990	90	9.57	4.00
5.30-12	B(4)	22.05	5.51	840	55	10.14	4.00
5.30-12	C(6)	22.05	5.51	1045	80	10.56	4.00
5.30-12	D(8)	22.05	5.51	1225	100	10.70	4.00



QH401

TIRE SIZE TUBELESS	LOAD RANGE/PLY	TIRE DIAMETER INCHES	SECTION WIDTH INCHES	MAX LOAD LBS	INFLATION PSI	WEIGHT LBS	RIM WIDTH INCHES
16.5 × 6.50-8	B(4)	16.57	6.73	620	45	7.30	5.38
16.5 × 6.50-8	C(6)	16.57	6.73	795	70	7.70	5.38
16.5 × 6.50-8	D(8)	16.57	6.73	915	90	7.91	5.38
18.5 × 8.50-8	B(4)	18.70	8.70	770	35	12.47	7.00
18.5 × 8.50-8	C(6)	18.70	8.70	940	50	12.91	7.00
18.5 × 8.50-8	D(8)	18.70	8.70	1070	65	13.16	7.00
20.5 × 8.0-10	B(4)	20.91	8.31	905	35	13.38	6.00
20.5 × 8.0-10	C(6)	20.91	8.31	1105	50	14.06	6.00
20.5 × 8.0-10	D(8)	20.91	8.31	1330	70	14.70	6.00
20.5 × 8.0-10	E(10)	20.91	8.31	1535	90	16.54	6.00
20.5 × 8.0-10	F(12)	20.91	8.31	1760	110	16.42	6.00
18 × 850-8A Tube(T)	A(2)	17.24	8.66	515	10	8.47	7.00
18 × 850-8A Tubeless(TL)	A(2)	17.24	8.66	515	10	10.22	7.00
18 × 850-8B(T)	B(4)	17.24	8.66	815	22	8.92	7.00
18 × 850-8B(TL)	B(4)	17.24	8.66	815	22	10.84	7.00
18 × 850-8C(T)	C(6)	17.24	8.66	1050	34	9.55	7.00
18 × 850-8C(TL)	C(6)	17.24	8.66	1050	34	10.67	7.00
205/50-10B(TL)	B(4)	18.15	8.03	665	30	11.16	6.00
205/50-10D(TL)	D(8)	18.15	8.03	970	51	12.80	6.00



QH402

Industrial Tractors Tires

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10.0/75-15.3	10	760	264	9.0	1180	470
11.5/80-15.3	12	865	290	9.0	1700	475



R4



R4

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10.5/80-18	10	912	274	9.0	1630	350
12.5/80-18	12	1001	350	11	2625	370

R4

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
16.9-24	8	1236	429	15	3250	260
16.9-28	12	1435	430	15	3450	260
17.5L-24	10	1241	445	15	1900	190
19.5L-24	12	1314	495	17	3455	230
21L-24	12	1402	533	18	3075	250



QH600

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10.0/75-15.3	12	760	264	9.00	1700	4.7





Implement Trailer Tires IMP700 Tubeless

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
10.0/80-12	8	710	264	9.0	1250	390
10.0/75-15.3	10	760	264	9.0	1525	390
11.5/80-15.3	12	865	290	9.0	2145	410
12.5/80-15.3	14	875	307	9.0	2810	510
13.0/65-18	14	890	336	11.0	2575	430



IMP700

OTR Tires

Size	Ply	Overall Diameter (mm)	Section Width(mm)	Rim	Load Capacity (kgs)	Inflated Pressure (kpa)
1300-24	12	1280	330	8	5600	450
	16				6000	525
1400-24	12	1350	360	8	6300	425
	16				7300	550
	20				8500	700
	24				9500	850
15.5-25	12	1275	395	12	6150	350
	16				7300	475
17.5-25	12	1350	445	14	8250	350
	16				9500	450
23.5-25	16	1615	595	19.5	8000	300
	20				10900	375
	24				12500	475



G2

Size	Rim	Ply	Section Width(mm)	Overall Diameter	Load Capacity (kgs)	Inflated Pressure (kpa)
14.00-24	10.00	16	375	1370	4000	375
14.00-24	10.00	20	375	1370	4625	475
14.00-24	10.00	24	375	1370	5150	575
15.5-25	12.00	10	395	1275	3000	225
15.5-25	12.00	12	395	1275	3250	250
16.00-24	11.25	16	430	1490	4875	325
16.00-24	11.25	20	430	1490	5450	400
16.00-24	11.25	24	430	1490	6000	475
16.00-25	11.25	32	430	1490	12500	875
17.5-25	14.00	12	445	1350	3560	225
17.5-25	14.00	16	445	1350	4250	300
17.5-25	14.00	20	445	1350	5000	400
18.00-25	13.00	36	495	1615	16000	850
20.5-25	17.00	16	520	1490	5450	275
20.5-25	17.00	20	520	1490	6000	325
20.5-25	17.00	24	520	1490	6700	400
23.5-25	19.5	16	595	1615	6150	225
23.5-25	19.5	20	595	1615	7300	300
23.5-25	19.5	24	595	1615	8000	350
26.5-25	22.00	20	645	1743	8250	250
26.5-25	22.00	24	645	1743	9250	300
26.5-25	22.00	28	645	1743	10000	350
29.5-25	25.00	28	750	1850	17500	425



L3/E3

Forklift Tires

Size	Rim	Ply	Section Width(mm)	Overall Diameter	Load Capacity (kgs)	Inflated Pressure (kpa)
5.00-8	3.00D	10	137	470	1290	1000
6.00-9	4.00E	10	160	540	1680	860
6.50-10	5.00F	10	175	510	2170	510
7.00-9	5.00S	10	190	590	2145	850
7.00-12	5.00S	12	190	676	2720	860
7.50-15	6.00	12	215	808	2650	790
8.25-12	7.00	12	235	696	2850	790
8.25-15	6.50	14	235	840	3700	800
28x9-15	7.0	12	230	700	3035	700



QH201



PNEUMATIC SHAPED SOLID TYRE



QH202



QH303



QH304

Size	Rim	Ply	Section Width(mm)	Overall Diameter	Load Capacity (kgs)	Inflated Pressure (kpa)
12.00-20	8.5	20	315	1125	10640	900
10.00-20	7.5	16	278	1055	8320	830

PRESS-ON SOLID TIRE

Size		MAX LOAD (KGS)				
		Counterbalanced Lift Truck				Other Industrial 16km/h
Inch	mm	10km/h		16km/h		
		LOAD	ROTATION	LOAD	ROTATION	
10-5*6 1/2	254*127*165.1	940	850	910	840	730
14*4 1/2*8	356*114*203.2	1090	965	1040	960	960
15 1/2*6*10	394*152*254	1735	1540	1660	1535	1335
16*5*10 1/2	406*127*266.7	1400	1250	1340	1240	1080
16*6*10 1/2	406*152*266.7	1780	1580	1700	1570	1370
16 1/4*5*11	413*127*285.8	1415	1260	1350	1250	1090
16 1/4*6*11	413*152*285.8	1780	1580	1710	1580	1370
18*6*12 1/8	457*152*308	1950	1740	1860	1720	1500
18*7*12 1/8	457*178*308	2370	2110	2270	2100	1820
18*8*12 1/8	457*203*308	2790	2480	2670	2470	2150
21*6*15	533*152*381	2280	2020	2160	2000	1740
21*7*15	533*178*381	2670	2380	2550	2360	2050
21*8*15	533*203*381	3110	2795	3000	2780	2420
22*12*16	559*305*406.4	5235	4660	5000	4630	4030
22*9*16	559*229*406.4	3750	3340	3590	3320	2890
9*5*5	229*127*127	890	790	850	785	680



QH301



QH302

Size	Rim	Pneumatic Shaped	Easy Fit Tires	Section Width (mm)	Overall Diameter	MAX LOAD (KGS)					Other Industrial 16km/h	
						Counterbalanced Lift Truck						
						10km/h		16km/h		25km/h		
LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION	LOAD	ROTATION			
3.50-8	3.00	●		118	350	1150	895	1120	815	1050	765	780
4.00-8	3.00	●		115	423	1055	845	1020	765	950	715	730
4.00-8	3.75	●		115	423	1050	845	1020	765	950	715	730
5.00-8	3.00	●	●	126	469	1210	970	1175	880	1095	820	840
6.00-9	4.00	●	●	140	545	1920	1535	1855	1390	1730	1295	1325
6.50-10	5.00	●	●	157	597	2640	2110	2545	1910	2370	1780	1820
7.00-9	5.00	●	●	170	578	2730	2015	2605	1925	2530	1790	1940
7.00-12	5.00	●	●	168	683	3015	2410	2910	2185	2710	2035	2075
7.00-15	5.50	●	●	178	759	3590	2870	3465	2600	3225	2420	2475
7.00-15	6.00	●	●	178	759	3590	2870	3465	2600	3225	2420	2475
16*6-8	4.33	●	●	156	418	1500	1200	1445	1085	1345	1010	1035
18*7-8	4.33	●	●	165	457	2350	1880	2265	1700	2110	1585	1620
21*8-9	6.00	●	●	189	535	2810	2250	2715	2035	2530	1895	1940
23*9-10	6.50	●	●	200	595	3420	2735	3300	2475	3076	2305	2355
27*10-12	8.00	●	●	236	683	4465	3570	4315	3235	4020	3015	3080
825-15	6.50	●	●	205	847	4940	3950	4765	3575	4440	3330	3405
825-12	5.00	●		206	735	3325	2660	3215	2410	2995	2245	2295
28*9-15	7.00	●	●	207	706	4090	3270	3945	2960	3675	2755	2820
250-15	7.00	●	●	226	735	4675	3740	4515	3385	4250	3155	3225
250-15	7.50	●		226	735	4675	3740	4515	3385	4250	3155	3225