

AGRICULTURE TYRE



TAISHAN TYRE

PROFESSIONAL AGRICULTURE TYRE MANUFACTURER





TAISHAN TYRE. FARM THE WORLD

TAISHAN AGRICULTURE TYRE PATTERN



TS19 R-1

7.50-18
11-38
12.4-28
13.6-28
18.4-30
18.4-34
18.4-38

TS21 R-1

5.50-17
6.00-12
6.00-16
6.50-16
7.50-16
7.50-20
8.3-20
8.3-24
9.5-20
9.5-24

TS47 R-1

13.6-24 16.9-38
13.6-38 18.4-34
14.9-24 18.4-38
15.5-38 18.4-42
16.9-24 20.8-38
16.9-28 23.1-30
16.9-30 23.1-26
16.9-34

TS48 R-1

10-15
15-24
16/70-20

TS58 R-1

11.2-28
12-38
14.9-26
14.9-28
18.4-26

TS59 R-1

10.75-15.3
11.2-20
11.2-24
12.4-24
14.9-30
12.4-32

TS66 R-1

11.2-24
11.2-38
13.6-24
14.9-24



TS79 R-1

15.5/80-24
14.00-38

TS22 R-2

9.5-24

TS49 R-2

5.50-17 11.2-24
6.00-12 12.00-18
6.50-16 12.4-26
7.50-16 12.4/11-28
8.3-20 13.6-38
8.3-24 14.9-30
9.5-24 16.9-34
11-32

TS50 R-2

19.5L-24
23.1-26
28L-26

TS71 R-2

23×10-10

TS73 R-4

16.9-28
7.50-16
12.9-18
16.9-24
17.5L-24
19.5L-24
21L-24

TS73A R-4

7.50-16
12.9-18
16.9-24
17.5L-24
19.5L-24
21L-24

TS77 R-4

10.0/75-15.3



TS78 R-4

10.5/80-18
12.5/80-18

TS23 F-2

4.00-12 6.00-16
4.00-14 6.50-16
4.00-16 6.50-20
5.00-15 7.50-16
5.00-15 7.50-20
5.50-16

TS26 I-1

9.5L-15
10-15
11L-15

TS55 G-2

26×7.5-12
11.2-20

TS8 LUG

4.00-8
4.00-12
4.00-14
4.00-16
4.50-16
5.50-16
6.50-16

TS69 IM-2

12.00-18

TS71A HF-3

54×68





TS19 R-1

Good traction and control performance;
Good wear and puncture resistance,
Good self-cleaning performance

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
7.50-18	6	TT		14	0.55	5.50F	—	203	7.99	850	33.46	950	225
	8											1135	270
11-38	6	TT		32	1.26	W10	DW10	305	12.01	1540	60.63	1400	140
	8											1545	160
12.4-28	6	TT		34	1.34	W11	W10、W10H	315	12.40	1260	49.61	1275	170
	8											1510	230
	10											1700	280
	12											1830	320
13.6-28	6	TT		37	1.46	W12	W11	345	13.58	1310	51.55	1430	160
	8											1645	200
	10											1910	250
	12											2125	300
18.4-30	6	TT		37	1.46	W16L	W15L、DW16	467	18.39	1550	61.02	2120	110
	8											2415	140
	10											2815	180
	12											3180	230
18.4-34	6	TT		37	1.46	W16L	W15L、DW16	467	18.39	1655	65.16	2250	110
	8											2565	140
	10											2990	180
	12											3375	230
18.4-38	6	TT		37	1.46	W16L	W15L	467	18.39	1755	69.09	2380	110
	8											2715	140
	10											3165	180
	12											3575	230
	14											3840	260

Note: For R-1 Pattern

1. When the tyre was used in front axle(driving wheel), tyre's maximum load and relative pressure applicable ,too.
2. When Max speed 30km/h, Max Load 100%; When speed 25km/h, load increase 15%; when speed 20km/h , load increase 35%; When speed 10km/h, load increase 50%; When speed 35km/h, load reduce 10%; When speed 40km/h, load reduce 20%.



TS21 R-1

Good traction and control performance;
Good wear and puncture resistance,
Good self-cleaning performance

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
5.50-17	6	TT		22	0.87	4.00E	—	138	5.43	750	29.53	400	280
6.00-12	6	TT		20	0.79	4.50E	5.00F	165	6.50	640	25.20	405	250
	8											450	300
6.00-16	6	TT		30	1.18	4.50E	5.00F	165	6.50	745	29.33	495	250
	8											550	300
6.50-16	6	TT		24	0.94	5.00F	4.50E、5.50F	180	7.09	765	30.12	565	250
	8											620	300
7.50-16	6	TT		25	0.98	5.50F	5.00F、6LB	205	8.07	810	31.89	650	210
	8											730	260
7.50-20	6	TT		24	0.94	5.50F	5.00F、6.00F	205	8.07	910	35.83	760	210
	8											860	260
8.3-20	6	TT		28	1.10	W7	W6	210	8.27	895	35.24	695	240
	8											785	300
8.3-24	6	TT		28	1.10	W7	W6	210	8.27	995	39.17	810	240
	8											920	300
9.5-20	6	TT		25	0.98	W8	W7、W8H	240	9.45	950	37.40	810	210
	8											955	280
9.5-24	6	TT		30	1.18	W8	W7、W8H	240	9.45	1050	41.34	940	210
	8											1110	280



TS79 R-1

Good cutting resistance;
Good traction and powerful grip performance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
15.5/80-24	12		TL	32	1.26	W13	—	394	15.51	1262	49.69	3000	300
	14											3300	340
14.00-38	8	TT		38	1.50	W11	—	355	13.98	1580	62.21	2160	220



TS47 R-1

Good traction and control performance;
 Good wear and puncture resistance,
 Good self-cleaning performance



Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
13.6-24	6	TT		35	1.38	W12	W11, DW12	345	13.58	1210	47.64	1340	160
	8											1545	200
	10											1790	250
13.6-38	6	TT		35	1.38	W12	W11, DW11 Dw12	345	13.58	1565	61.61	1660	160
	8											1910	200
	10											2215	250
14.9-24	6	TT		33	1.30	W13	W12, DW12	378	14.88	1265	49.80	1510	140
	8											1760	180
	10											1990	230
15.5-38	6	TT		37	1.46	W14L	DW14	395	15.55	1570	61.81	1765	140
	8											2060	180
	10											2320	230
16.9-24	6	TT		37	1.46	W15L	DW14, W14L	430	16.93	1335	52.56	1725	130
	8											2040	170
	10											2230	200
16.9-28	6	TT		37	1.46	W15L	DW14, W14L	430	16.93	1435	56.50	2410	230
	8											1840	130
	10											2175	170
16.9-30	6	TT		37	1.46	W15L	DW14, W14L	430	16.93	1485	58.46	2380	200
	8											2580	230
	10											1900	130
16.9-34	6	TT		39	1.54	W15L	DW14, W14L	430	16.93	1585	62.40	2245	170
	8											2455	200
	10											2730	240
16.9-38	6	TT		44	1.73	W15L	DW14, W14L	430	16.93	1685	66.34	2015	130
	8											2380	170
	10											2605	200
18.4-34	6	TT		37	1.46	W16L	W15L, DW16	467	18.39	1655	65.16	2820	230
	8											2950	250
	10											2130	130
18.4-38	6	TT		37	1.46	W16L	W15L	467	18.39	1755	69.09	2520	170
	8											2760	200
	10											2990	230
18.4-42	6	TT		37	1.46	W16L	W15L	467	18.39	1857	73.11	3130	250
	8											2250	110
	10											2565	140
20.8-38	6	TT		40	1.57	W18L	—	528	20.79	1835	72.24	2990	180
	8											3375	230
	10											3630	260
23.1-30	6	TT		40	1.57	DW20	—	587	23.11	1705	67.13	2380	110
	8											2715	140
	10											3165	180
23.1-26	6	TT		40	1.57	DW20	—	587	23.11	1605	63.19	3575	230
	8											3840	260
	10											2575	140
	12											3000	180
	14											3400	220
	16											3660	250
	18											3900	280
	20											3090	130
	22											3475	160
	24											4000	200
	26											4450	240
	28											4860	280
	30											3035	110
	32											3460	140
	34											3850	170
	36											2850	110
	38											3245	140
	40											3610	170
	42											3970	200



TAISHAN TYRE. FARM THE WORLD



TS48 R-1

Application to combined harvester;
Good load capacity, good wear and cutting and puncture resistance;
Good traction and self-cleaning performance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
10-15	6	TT		22	0.87	9.00×15.3	—	260	10.24	760	29.92	755	230
	8											950	310
	10											1090	390
	12											1180	470
15-24	10	TT		33	1.30	DW14	W14	410	16.14	1330	52.36	2800	280
	12											3020	320
	14											3160	350
16/70-20	10	TT		33	1.30	13.0/1.0	—	410	16.14	1075	42.32	2310	250



TS58 R-1

Good traction and control performance;
Good wear and puncture resistance,
Good self-cleaning performance

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
11.2-28	6	TT		35	1.38	W10	W9、W10H	285	11.22	1205	47.44	1115	180
	8											1305	240
	10											1500	300
12-38	8	TT		38	1.50	DW11	W11	330	12.99	1575	62.01	1570	140
	10											1760	200
	12											1950	240
14.9-26	6	TT		36	1.42	W13	W12、DW12	378	14.88	1315	51.77	1560	140
	8											1820	180
	10											2055	230
14.9-28	6	TT		38	1.50	W13	W12	378	14.88	1365	53.74	1610	140
	8											1880	180
	10											2120	230
	12											2370	280
14.9-30	6	TT		38	1.50	W13	W12、DW12	378	14.88	1415	55.71	1665	140
	8											1940	180
	10											2190	230
18.4-26	6	TT		37	1.46	DW16	W15L	467	18.39	1450	57.09	1990	110
	8											2265	140
	10											2645	180
	12											2985	230



TS59 R-1

Good wear and puncture resistance,
Good self-cleaning performance

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
10.0/75-15.3	10	TT		30	1.18	9.00	—	264	10.39	910	35.83	1525	390
11.2-20	6	TT		30	1.18	W10	W9, W10H	285	11.22	1005	39.57	920	180
	8											1085	240
11.2-24	6	TT		33	1.30	W10	W9, W10H	285	11.22	1105	43.50	1045	180
	8											1225	240
	10											1380	300
12.4-24	6	TT		34	1.34	W11	W10, W10H	315	12.40	1160	45.67	1200	170
	8											1415	230
	6											1275	170
12.4-28	8	TT		34	1.34	W11	W10, W10H	315	12.40	1260	49.61	1510	230
	10											1700	280
	12											1830	320
	4											1070	110
12.4-32	6	TT		36	1.42	W 11	W 10	315	12.40	1360	53.54	1355	170
	8											1605	230
	10											1800	280



TS66 R-1

Irrigation Tire
Application to mobile irrigation system equipment;
Good traction and self-cleaning performance ;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
11.2-24	6	TT		25	0.98	W10	W9, W10H	285	11.22	1105	43.50	1045	180
	8											1225	240
11.2-38	6	TT		25	0.98	W10	—	285	11.22	1448	57.01	950	120
	8											1150	180
	10											1350	250
13.6-24	6	TT		25	0.98	W12	W11, DW12	345	13.58	1210	47.64	1340	160
	8											1545	200
14.9-24	6	TT		26	1.02	W13	W12, DW12	378	14.88	1265	49.80	1510	140
	8											1760	180



TAISHAN TYRE. FARM THE WORLD



TS22 R-2

Application to tractors operated in cane, rice, muddy and wet field farming;
 Deep pattern provide excellent and powerful traction and self-cleaning performance;
 Good design for long-wearing, tear-resistance and cracking resistance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
9.5-24	6	TT		60	2.36	W8	W7 W8H	240	9.45	1150	45.28	1315	240



TS50 R-2

Application to tractors operated in cane, rice, muddy and wet field farming;
 Deep pattern provide excellent and powerful traction and self-cleaning performance;
 Good design for long-wearing, tear-resistance and cracking resistance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
19.5L-24	8	TT		92	3.62	W17	—	495	19.49	1345	52.95	1900	140
	10											2120	170
	12											2360	210
23.1-26	8	TT		89	3.50	DW20	—	587	23.11	1660	65.35	2850	110
	10											3245	140
	12											3610	170
	14											3970	200
28L-26	10	TT		93	3.66	DW25	—	715	28.15	1615	63.58	3460	120
	12											3785	140
	14											4245	170



TS49 R-2

Application to tractors operated in cane, rice, muddy and wet field farming;
 Deep pattern provide excellent and powerful traction and self-cleaning performance;
 Good design for long-wearing, tear-resistance and cracking resistance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
5.50-17	6	TT		50	1.97	4.00E	—	138	5.43	798	31.42	400	280
6.00-12	6	TT		50	1.97	4.50E	5.00F	165	6.50	690	27.17	425	270
6.50-16	6	TT		60	2.36	5.00F	—	170	6.69	810	31.89	600	270
7.50-16	6	TT		63	2.48	5.50F	5.00F	200	7.87	895	35.24	650	210
8.3-20	6	TT		62	2.44	W7	W6	210	8.27	950	37.40	970	270
8.3-24	6	TT		72	2.83	W7	W6	210	8.27	1050	41.34	1135	270
9.5-24	6	TT		80	3.15	W8	W7, W8H	240	9.45	1150	45.28	1315	240
11-32	6	TT		90	3.54	W10	DW10	305	12.01	1490	58.66	1080	160
11.2-24	6	TT		82	3.23	W10	W9, W10H	285	11.22	1205	47.44	1465	210
12.00-18	10	TT		60	2.36	9.00V	—	327	12.87	1090	42.91	1800	350
	12											1950	420
12.4-26	6	TT		83	3.27	W11	W10/, 10H	315	12.40	1265	49.80	1240	160
12.4/11-28	6	TT		83	3.27	W11	W10, W10H	315	12.40	1315	51.77	1785	200
	6											2160	160
13.6-38	8	TT		85	3.35	W12	W11, DW11 DW12	345	13.58	1710	67.32	2675	230
	10											2975	280
14.9-30	10	TT		90	3.54	W13	—	378	14.88	1495	58.86	2190	230
16.9-34	8	TT		90	3.54	W15L	DW14, W14L	430	16.93	1670	65.75	2380	170
	10											2605	200



TS71 R-2

Application to tractors operated in cane, rice, muddy and wet field farming;
 Deep pattern provide excellent and powerful traction and self-cleaning performance;
 Good design for long-wearing, tear-resistance and cracking resistance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
23×10-10	4		TL	25	0.98	8.00I	—	254	10.00	600	23.62	385	60



TS73 R-4

Application to agricultural implement vehicles;
Application to be used on soft road, muddy road and desert;
Good traction performance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
16.9-28	10	TL	28	1.10	W15L	W14L	430	16.93	1410	55.51	2380	200	
	12										2730	240	



TS73A R-4

Application to agricultural implement vehicles;
Application to be used on soft road, muddy road and desert;
Good traction performance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
7.50-16	6	TT		18	0.71	5.50F	—	205	8.07	765	30.12	650	210
12.9-18	10	TT		22	0.87	9.00V	—	327	12.87	1090	42.91	1800	350
16.9-24	8	TL	26	1.02	W15L	—	430	16.93	1309	51.54	2650	190	
	10										2900	220	
17.5L-24	10	TL	26	1.02	W15L	—	445	17.52	1241	48.86	2800	220	
	12										3075	260	
19.5L-24	10	TL	30	1.18	DW16A	—	495	19.49	1314	51.73	3000	190	
	12										3450	230	
21L-24	10	TL	30	1.18	DW18A	—	533	20.98	1378	54.25	3350	180	
	12										3875	220	





TS77 R-4

Application to agricultural implement vehicles;
Application to be used on soft road, muddy road and desert;
Good traction performance;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
10.0/75-15.3	4	TT		15	0.59	9.00	—	264	10.39	760	29.92	880	150
	6											1120	230
	8											1330	310
	10											1525	390



TS78 R-4

With good cutting resistance, powerful grip ability,
and good traction property.

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
10.5/80-18	8	TL		21	0.83	9	—	274	10.79	905	35.63	1710	300
	10											1935	370
	12											2375	310
12.5/80-18	12	TL		24	0.94	9	—	308	12.13	985	38.78	2625	370
	14											2910	430
	16											3130	490



TS23 F-2

Three rib design for all types of farming conditions;
Excellent guide and self-cleaning performance;
Good wear resistance, good control ability, long service life.

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
4.00-12	4	TT		8	0.31	3.00D	2.5C	110	4.33	535	21.06	250	340
4.00-14	4	TT		10	0.39	3.00D	2.5C	110	4.33	590	23.23	270	340
4.00-16	4	TT		12	0.47	3.00D	—	110	4.33	640	25.20	300	340
	6											420	380
5.00-15	4	TT		14	0.55	3.00D	—	130	5.12	645	25.39	365	280
	6											465	420
5.00-15	4	TT		14	0.55	4J	4.00E, 3.00D	140	5.51	665	26.18	365	280
	6											465	420
5.50-16	6	TT		14	0.55	4.00E	4.50E	150	5.91	710	27.95	525	370
	4											450	230
6.00-16	6	TT		14	0.55	4.00E	4.50E, 5.00F 5K	160	6.30	740	29.13	560	340
	8											675	450
	4											510	230
6.50-16	6	TT		14	0.55	4.50E	4.00E, 5.00F 5K	175	6.89	760	29.92	615	310
	8											735	420
	6											600	230
6.50-20	8	TT		14	0.55	5.00F	4.50E, 5.50F	180	7.09	860	33.86	725	310
	10											865	420
	4											605	200
7.50-16	6	TT		21	0.83	5.50F	5.00F, 5K 6.00F, 6LB	205	8.07	810	31.89	745	280
	8											870	370
	4											710	200
7.50-20	6	TT		21	0.83	5.50F	5.00F	205	8.07	910	35.83	875	280
	8											1070	370

Note: For F-2 Pattern

When Max speed 30km/h, Max Load 100%; When speed 25km/h, load increase 15%, when speed 20km/h, load increase 35%; When speed 10km/h, load increase 50%; When speed 35km/h, load reduce 10%
When speed 40km/h, load reduce 20%.



TS26 I-1

Application to farm implement and wagons and trailers;
Good guide performance, less rolling resistance,
good wear resistance, high floating force;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
9.5L-15	6		TL	7	0.28	8LB	—	240	9.45	765	30.12	895	190
	8											1100	280
10-15	6		TL	9	0.35	9.00×15.3	—	264	10.39	760	29.92	1110	230
	8											1330	310
11L-15	6	TT	TL	7	0.28	W8L	10LB、8LB W10L	280	11.02	775	30.51	950	170
	8											1130	220
	10											1285	280



TS55 G-2

Application to garden tractors;
With smooth tread, bigger ground, High floating force;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
26×7.5-12	4	TT		7	0.28	5.00F	—	205	8.07	640	25.20	455	147
11.2-20	4	TT		10	0.39	W10	W9、W10H	295	11.61	995	39.17	785	120

Note: Max speed is 16km/h



TS8 LUG

Application to tractor front tire;
Good traction performance and control ability;
good wear resistance, with side-skidding resistance.

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
4.00-8	4	TT		6.5	0.26	3.00D	2.5C	112	4.41	415	16.34	225	275
4.00-12	4	TT		7	0.28	3.00D	2.5C	112	4.41	520	20.47	300	275
4.00-14	4	TT		10	0.39	3.00D	—	122	4.80	655	25.79	700	400
4.00-16	4	TT		12	0.47	3.00D	—	110	4.33	640	25.20	300	340
	6											420	380
4.50-16	8	TT		9	0.35	3.00D	—	122	4.80	655	25.79	700	400
5.50-16	8	TT		7	0.28	4.00E	4.50E	150	5.91	685	26.97	800	360
	10											950	420
6.50-16	10	TT		10	0.39	4.50E	4.00E 5.00F	173	6.81	735	28.94	1000	530

Note

1. When the max speed is 30km/h, the max load is 100%; when speed is 10km/h, load can increase 20% and increase 30% pressure.
2. When farm trailer to go on the blacktop, the speed not over 30km/h, allow load to increase 20% and increase 30% pressure.



TS69 IM-2

Suitable to be used on the harsh road surface in areas like quarry and mine, etc.

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
12.00-18	10	TT		19	0.75	9.00V	—	327	12.87	1090	42.91	1800	350
	12											1950	420



TS71A HF-3

Application in desert and marsh areas; minimal damage to the environment; Amphibian tyre, excellent stability, traction and self-cleaning performance; Provides flotation necessary to minimize compaction and rutting;

Tire Size	Ply Rating	TYPE		Bar Height		Standard Rim	Available Rim	Inflated Dimensions				Max Load kg	Pressure Kpa
		TT	TL	mm	Inch			Section Width		Overall Diameter			
								mm	Inch	mm	Inch		
54×68	20		TL	39	1.54			1715	67.52	1410	55.51	4535 5000	120 170

Conversion Table for Inflation Pressure

kPa	bar	lb/in ² (p.s.i.)	Kg/cm ² *
25	0.25	3.6	0.25
50	0.5	7.3	0.51
75	0.75	11	0.76
100	1.0	15	1.0
150	1.5	22	1.5
200	2.0	29	2.0
250	2.5	36	2.6
300	3.0	44	3.1
350	3.5	51	3.6
400	4.0	58	4.1
450	4.5	65	4.6
500	5.0	73	5.1
550	5.5	80	5.6
600	6.0	87	6.1
650	6.5	94	6.6
700	7.0	102	7.1
750	7.5	109	7.7
800	8.0	116	8.2
850	8.5	123	8.7
900	9.0	131	9.2
950	9.5	138	9.7
1000	10.0	145	10.2
1050	10.5	152	10.7

* The figures in columns of p.s.i. and kg/cm²* are the nearest round numbers



ISO14001

ISO9001

Ece

Dot-1

Dot-2



TAISHAN TYRE

Shandong Taishan Tyre Co.,Ltd

No.001 Taixi Avenue, Feicheng City, Shandong, China

TEL: 0086-538-3269324/3269992

FAX: 0086-538-3269370/3161668

E-mail: tstyre@126.com, tstyreliu@vip.163.com

www.taishantyre.com